

# Rockfon® Hub™

- The platform brings multipurpose flexibility to your interiors by creating breakout spaces where people can think, work or talk in peace
- The soft island shapes can be enhanced with a felt frame cover, mood lighting and curtains to create calm or cosy areas where people can work productively without disturbance
- Rockfon® Hub™ is delivered as a complete kit contributing to easy and hassle-free installation

## Product Description

**Rockfon® Hub™ is available in 4 dimensions:**

- 3000 x 4800mm (small)
- 3600 x 4200mm (medium)
- 4800 x 4800mm (large)
- 4800 x 7200mm (extra large)
















Black anodized frame in an organic shape.


Felt in three different colors: light grey, dark grey, white.

Pre-selected concealed tiles: white with Rockfon Blanka® or colours with Rockfon Color-all®.

## Application Areas

- Office
- Leisure
- Education
- Retail


Grid Product Group	Product image	Component description	Length x Width x Height (mm)	Pieces per packaging	Weight per packaging
		Rockfon Blanka®	600 x 600 x 22	10	13.3 kg
		Rockfon Color-all®		10	13.3 kg
HUB FRS		Frame Profile Straight	1800 x 35 x 110	2	8.2 kg
			2400 x 35 x 110	2	11 kg
			3000 x 35 x 110	2	13.8 kg
			3600 x 35 x 110	2	16.5 kg
HUB FRC		Frame Profile Corner	1066 x 35 x 110	4	9.8 kg
HUB CAS		Carrier Profile	2976 x 40 x 40	1	6 kg
			3576 x 40 x 40	1	7.2 kg
			Carrier Profile Extension	1200 x 40 x 40	1
		Carrier Profile Floating End	868 x 40 x 40	1	1.8 kg
HUB CON		Frame Profile Coupling			
HUB SCREW M6		Coupling Screw			
HUB CON		Profile Connector			
		Inter Connector R			
		Intersection Clip			
HUB HHSS		M6 Hammer Head Screw			
HUB WIRE		Vertical Wire Set			
		Bracing Wire Set			
HUB GLI		Curtain Rollers			
HUB FELT		Felt Cover			
T24 MR CL&HK		Main runner T24 Click / Hook	3600 x 24 x 38	15	19.5 kg
T24 CT CLICK		Cross tee T24 Click	600 x 24 x 38	45	8.2 kg
HUB MOLD		Cutting template		1	0.5 kg



## Performance



**Sound absorption**  
 $\alpha_w$ : 0,95 (Class A)



Edge /  
 Thickness (mm) /  
 Suspension (incl. tile - mm)

	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	$\alpha_w$	Absorption class	NRC
Blanka X: 22 / 200	0.55	0.85	0.95	0.90	1.00	1.00	0.95	A	0.95
Blanka X: 22 / 1000	0.55	0.75	0.90	1.00	1.00	1.00	0.95	A	0.95
Color-all X: 22 / 200	0.45	0.85	0.90	0.90	1.00	1.00	0.95	A	0.95



**Reaction to fire**  
 A1  
 (tiles and grid components)



**Environment**  
 Fully recyclable stone wool  
 The recycled content of Rockfon tiles is between 29% and 64% according to ISO 14021.  
 Rockfon tiles are Cradle to Cradle Certified® Silver and Bronze (depending on product type).



**Cleaning**  
 - Vacuum










**Indoor environment**  
 A selection of Rockfon tiles have been awarded the Finnish M1 emission classification for building materials and the Danish Indoor Climate Label for low emission products



**Hygiene**  
 Stone wool provides no sustenance to microorganisms



## Colours



NCS codes are closest colour match. The actual colour of the islands may deviate slightly from printed colours due to the texture of the surface and the underlying colour of stone wool.

## Felt Cover

